SOUNDERS & BEACONS (VADS)



Hi-Output Wall Beacon/Sounder
Part Number CON433A/CX/DR

Hi-Output Wall Beacon c/w 103dB(A) Sounder (deep base), CON433A/CX/DR

- Third-party certified to EN54-3 (Sounders), EN54-23 (VADs) and 17 (Isolators) by the LPCB.
- Provides 'W-2.4-8.2' light distribution when wall mounted (min 0.4 lux over a 2.4m x8.2m cuboid area).
- Impressive 103dB(A) sound output @ 1m.
- Onboard short-circuit loop isolator.
- 550µA quiescent current.
- 14mA alarm current @24V DC (VAD lit, sounder on max).
- Group addressing facility allows multiple devices to be operated simultaneously.
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP33C (Type B) rated.



LPCB Hi-Output Wall Sounder
Part Number CON430A/CX/DR

Hi-Output 103dB(A) Wall Sounder (deep base), CON430A/CX/DR

- Third-party certified to EN54-3 (Sounders) and 17 (Isolators) by the LPCB.
- Impressive 103dB(A) sound output @ 1m.
- Onboard short-circuit loop isolator.
- 550µA quiescent current.
- 5mA alarm current @24V DC (sounder on max).
- Group addressing facility allows multiple devices to be operated simultaneously.
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP33C (Type A) rated.



Hi-Output Wall Beacon/Sounder Part Number CON433A/CX/DR/65

Hi-Output Wall Beacon c/w 103dB(A) Sounder, IP65, CON433A/CX/DR/65

- Powerful 103dB(A) sound output @ 1m
- W-2.4-8.2 light distribution
- Weather resistant to IP65
- Onboard short-circuit loop isolator.
- Group addressing facility allows multiple devices to operate simultaneously
- 14mA alarm current @24V DC
- 550uA quiescent current
- 114mm diameter, 132mm deep

Hi Output 103dR(A) Wall Soun



Hi-Output Wall Sounder
Part Number CON430A/CX/DR/65

Hi-Output 103dB(A) Wall Sounder, IP65, CON430A/CX/DR/65

- 103dB(A) sound output @ 1m
- Weather resistant to IP65
- Onboard short-circuit loop isolator.
- Group addressing facility allows multiple devices to operate simultaneously
- 5mA alarm current @24VDC
- 7 selectable volume levels
- Up to 15 selectable tone pairs
- 550uA quiescent current
- 114mm diameter, 132mm deep