



	<h2 style="text-align: center;">Addressable Smoke Detector AW-D301 Data Sheet</h2>
Operating Voltage	Loop 24V(18V~28V)
Standby Current	<0.3mA
Alarm Current	<1.5mA (without remote indicator) <3.5mA (with remote indicator)
Fire LED	Red, Flash in polling, and illuminate in alarming.
Remote indicator output	Polarity-sensitive output, directly connect to remote indicator (built in 10k resistor in series, max. output current is 2mA); The red indicator will blink in the monitoring status or remain lit in the alarm status.
Programming	Electronically addressed.
Programming Range	Occupying one address within 1~324.
Wiring	Loop: two wire, polarity-insensitive
Environmental Temperature	-10℃~+55℃
Relative Humidity	≤95%, non-condensing
Material of Enclosure	ABS
Dimension	Diameter: 100mm Height: 58mm (with the base)
Mounting Hole Distance	44.5mm~64.3mm
Weight	About 128g(with base)
Certificate	<div style="text-align: center;">   </div> <p style="text-align: center;">0832-CPR-F2509    1426c/01</p>



**ASENWARE LTD**  
 ADDRESS: 6 PROSPECT WAY, ROYAL OAK INDUSTRIAL ESTATE DAVENTRY,  
 NORTHAMPTONSHIRE, ENGLAND, NN118PL  
 WEBSITE: [www.asenware.com](http://www.asenware.com)    EMAIL: [info@asenware.com](mailto:info@asenware.com)