
	<h2>Addressable Manual Call Point</h2> <h3>AW-D305</h3> <h3>Data Sheet</h3>
Operating Voltage	Loop 24V (18V~28V)
Standby Current	<0.3mA
Alarm Current	<2mA
Indicator	Red alarm indicator flashes when data logging, press the manual button lit work
Type of Initiating Part	Reusable
Initiating Mode	Pressing the frangible element manually
Resuming Mode	Manually resumed by a special key
Programming Mode	Electronically addressed
Address Range	One address within 1~324.
Wiring	Polarity-insensitive two-wire
Class	Type A, indoors.
Ingress Protection Rating	IP43
Environmental Temperature	-10°C~+55°C
Relative Humidity	≤95%, non-condensing



**ASENWARE LTD**

ADDRESS: 6 PROSPECT WAY, ROYAL OAK INDUSTRIAL ESTATE DAVENTRY,  
NORTHAMPTONSHIRE, ENGLAND, NN118PL

Material of Enclosure	ABS
Dimension (L×W×H)	90mm×90mm×42mm (overall height) 90mm×90mm×23mm (exposed after installation dimensions)
Mounting Hole Distance	60mm ~ 62.5mm
Weight	About 95g
Certificate	  0832-CPR-F2510 1426d/01



**ASENWARE LTD**

ADDRESS: 6 PROSPECT WAY, ROYAL OAK INDUSTRIAL ESTATE DAVENTRY,  
NORTHAMPTONSHIRE, ENGLAND, NN118PL