SUPERFIRE JUNIOR

Selectable Gallonage Nozzle







UL LISTED & DNV-GL APPROVED

SUPERFIRE JUNIOR







Selectable Gallonage Nozzle

"SUPERFIRE JUNIOR" is a light-weight selectable gallonage nozzle with straight stream and 120° wide fog, setting at 4 different flows. Made from high strength aluminum with hard anodized treatment, this nozzle is designed to suit the exacting demands of the fireman. A simple shut-off lever, online flush function, pistol grip handle, easily replaceable spinning teeth ring, and protective rubber bumper make this product the perfect combination of rugged, flexibility and sophisticated features.



Features

- Selectable Multi flow settings: As per Table Below
- ▶ Shut off ball valve for nozzle operation.
- ▶ Jet-spray mode by twist rotation of bumper.
- ▶ Spray upto 120°.
- Abrasion and corrosion resistant.
- Flush without shutting off.
- ▶ Anti- slip finger lock rubber moulded pistol grip.
- ▶ Suitable for foam application with separate educator and foam tube.
- Standard Inlet: 1½" BSP NH (F) Swivel.
- ▶ Optional Inlet: 64mm 2½ "BS (M) Inst./Storz/JIS etc.
- ▶ Weight: 1.9 kgs (apprx.) with 1½" NH (F) Swivel.
 - 2.2 kgs (approx.) with 2½" BS:336 (M).

Performance @ 7 bar

Flow Settings :				
GPM	30	59	93	125
LPM	115	225	355	475



Head Office:

4, Champaklal Udyog Bhavan, Sion (E), Mumbai - 400 022. India. Tel.: +91-22-4351 1500 / 24077421 ● Fax: +91-22-2407 1320 E-mail: info@newagefireprotection.com ● Website: www.newagefire.co