



FYRFYTER



FYRFYTER SUPER


- Polyester Jacketted
- Black Synthetic Epdm Rubber Lining
- Burst Pressure - 50 kg/cm²
- Proof Pressure - 30 Kg/cm²
- Bearing IS : 636:88 Type A Mark
- Meets BS:6391 Type 1 & 2, DIN 14811, UL 219, EN 14540 (2004)
- Length - up to 60 Mts.

Salient Features :

- Jacket Is Made of 100% Polyester For Extra Strength.
- Unaffected By Fungus
- Heat And Abrasion Resistant
- Special Quality EPDM Rubber As Internal Lining To Withstand Heat And Polluted Water
- High Burst Pressure, Yet Quite Flexible Facilitating Operation
- Light In Weight, Yet Durable

SPECIFICATION

Diameter: mm. Inches	25 1	38 1.1/2	45 1.3/4	50 2	63 2.1/2	70 2.3/4	76 3	102 4	127 5	152 6
Burst Pressure kgf / cm² / bar / psi (Min.)	50 725	50 725	50 725	50 725	50 725	50 725	50 725	42 600	36 525	36 525
Proof Pressure kgf / cm² / bar / psi	30 435	30 435	30 435	30 435	30 435	30 435	30 435	25 360	20 290	20 290
Kink Test Pressure: kgf / cm² / bar / psi	30 435	30 435	30 435	30 435	30 435	30 435	30 435	25 360	20 290	20 290
Working Pressure kgf / cm² / bar / psi	17 250	17 250	17 250	17 250	17 250	17 250	17 250	15 215	12 175	12 175
30 m Length Coil Dia : cms.	45	45	45	45	45	45	50	50	55	55
Mass per meter : Gms.(Max.)	200	275	325	350	425	480	525	800	950	1100
Abrasion Resistance : Cycles (Min.) at 7 kgf/cm² Pressure	100	100	100	100	100	100	100	100	100	100
Heat Resistance : Sec. (Min.)	8	8	8	8	8	8	8	8	8	8



“Fyrfyter Super” Is Extra Strong And Abrasion Resistant, Having An External Coat Of Red Synthetic Elastomer, Providing Protection Against Moisture, Mildew, Fungus And Contact With Oils. Needs No Drying After Use.

COLORS

Standard-Red	Optional: Green, Blue, Yellow, Orange, Black (Minimum Quantity 3000 Mtrs.)				

Approval

- Bureau of India Standards
- GL, Wheelmark / MED

HEAD OFFICE :-